ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 1 / 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Engine Oil 0W - 20

Article number: 177649, 177650, 177651

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

Signal word none
Hazard statements none
Precautionary statements none

Special labelling EUH210 Safety data sheet available on request.

Contains: Calcium long-chain alkyl salicylate, Calcium sulfonate. EUH208 May produce an

allergic reaction.

2.3 Other hazards

Physico-chemical hazards No particular hazards known.

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

ebi

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 2 / 14

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
50 - < 100	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	1-Decene, homopolymer, hydrogenated
	CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 5	Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester
	CAS: 125643-61-0, EINECS/ELINCS: 406-040-9, EU-INDEX: 607-530-00-7, Reg-No.: 01-0000015551-76-XXXX
	GHS/CLP: Aquatic Chronic 4: H413
1 - < 5	Bis(nonylphenyl)amine
	CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX
	GHS/CLP: Aquatic Chronic 4: H413
0.1 - < 1	Calcium long-chain alkyl salicylate
	GHS/CLP: Skin Sens. 1B: H317
0.1 - < 1	Calcium sulfonate
	GHS/CLP: Skin Sens. 1B: H317

Comment on component parts For full text of H-statements and R-phrases: see SECTION 16.

All chemical substances in this material are included on or exempted from listing on the

IECSC Inventory.

Mixture containing mineral oil. Mineral oil with <3% DMSO extract according to IP 346.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of product entering the lungs.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet.

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 3 / 14

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx). Hydrogen sulfide ((H2S).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not smoke.

Wash hands before breaks and after work.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Take off contaminated clothing and wash before reuse.

Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container tightly closed. Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 4 / 14

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX

Long-term exposure: 5 mg/m³, oil mist

Short-term exposure (15-minute): 10 mg/m³

1-Decene, homopolymer, hydrogenated

CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX

Long-term exposure: 5 mg/m³, OSHA PEL

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance		
Bis(nonylphenyl)amine, CAS: 36878-20-3		
Industrial, dermal, Long-term - systemic effects, 5 mg/kg bw/day		
general population, dermal, Long-term - systemic effects, 2,5 mg/kg bw/day		
general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
general population, oral, Long-term - systemic effects, 740 μg/kg bw/day		
Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0		
Industrial, inhalative, Long-term - systemic effects, 2.33 mg/m³		
Industrial, inhalative, Acute - systemic effects, 1750 mg/m³		
Industrial, dermal, Long-term - systemic effects, 220 μg/kg bw/day		
Industrial, dermal, Acute - systemic effects, 20 mg/kg bw/day		
Industrial, dermal, Long-term - local effects, 6 µg/cm ²		
Industrial, dermal, Acute - local effects, 1 mg/cm ²		
general population, inhalative, Long-term - systemic effects, 740 μg/m³		
general population, inhalative, Acute - systemic effects, 875 mg/m³		
general population, dermal, Long-term - systemic effects, 330 μg/kg bw/day		
general population, dermal, Acute - local effects, 8.33 mg/cm ²		
general population, oral, Long-term - systemic effects, 160 μg/kg bw/day		
general population, oral, Acute - systemic effects, 50 mg/kg bw/day		

PNEC

Bis(nonylphenyl)amine, CAS: 36878-20-3 freshwater, 412 μg/L sediment (freshwater), 1 mg/kg sediment dw sediment (seawater), 0.1 mg/kg sediment dw	Substance	
seawater, 41.2 µg/L sediment (freshwater), 1 mg/kg sediment dw	Bis(nonylphenyl)amine, CAS: 36878-20-3	
sediment (freshwater), 1 mg/kg sediment dw	freshwater, 412 μg/L	
	seawater, 41.2 µg/L	
sediment (seawater), 0.1 mg/kg sediment dw	sediment (freshwater), 1 mg/kg sediment dw	
3. 3	sediment (seawater), 0.1 mg/kg sediment dw	-



Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 5 / 14

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

oral (food), 9,33 mg/kg

Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0

freshwater, 4.3 - 30 µg/L

seawater, 30 - 1800 ng/L

sewage treatment plants (STP), 1 - 100 mg/L

sediment (freshwater), 370 - 233000 µg/kg sediment dw

soil, 50 - 189000 µg/kg soil dw

sediment (seawater), 37 - 23300 µg/kg sediment dw

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

oral (food), 41.33 mg/kg food

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 6 / 14

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical stateliquidFormliquidColorgreenOdorcharacteristic

Odour threshold No information available.

pH-value not applicable

pH-value [1%]Boiling point or initial boiling point available.and boiling range [°C]No information available.

Flash point [°C] 230

Flammability not applicable

Lower explosion limitNo information available.Upper explosion limitNo information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] No information available.

Density [g/cm³] 0.84 (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water virtually insoluble

Solubility other solvents No information available.

Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity 42.3 mm²/s (40°C)

Relative vapour density No information available.

Melting point [°C] No information available.

Auto-ignition temperature [°C] No information available.

Decomposition temperature [°C] No information available.

Particle characteristics No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

No special measures necessary.



Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 7 / 14

10.5 Incompatible materials

Oxidizing agent Acids Strong basic compounds

10.6 Hazardous decomposition products

No hazardous decomposition products known.

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 8 / 14

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

LD50, oral, Rat, 2000 - 5000 mg/kg bw

LD50, oral, Rat, >5000 mg/kg, no adverse effect observed

Bis(nonylphenyl)amine, CAS: 36878-20-3

LD50, oral, Rat, 5000 mg/kg bw

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, oral, Rat, 5000 mg/kg bw

Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0

LD50, oral, Rat, 500 - 2000 mg/kg bw

Acute dermal toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

LD50, dermal, Rat, >2000 mg/kg bw, OECD 402

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0

LD50, dermal, Rat, 2000 mg/kg bw

Acute inhalational toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

LC50, inhalative, Rat, >5.2 mg/L air, OECD 403, no adverse effect observed

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

OECD 404, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4



Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 9 / 14

OECD 405, non-irritating

Respiratory or skin sensitisation

May produce an allergic reaction.

Calculation method

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

oral, Rat, no adverse effect observed

Bis(nonylphenyl)amine, CAS: 36878-20-3

NOEL, oral, Rat, 100 mg/kg bw/day

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m3 air

LOAEL, oral, Rat, 125 mg/kg bw/day

Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0

NOAEL, oral, Rat, 3 - 750 mg/kg bw/day

NOAEL, dermal, Rat, 500 - 1000 mg/kg bw/day

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance

1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

no adverse effect observed

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard

Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.



Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 10 / 14

11.2 Information on other hazards

11.2.1 Endocrine disrupting

properties

Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Substance		
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4		
EL50, (48h), Invertebrates, >1000mg/L		
NOELR, (21d), Invertebrates, 125mg/L		
NOELR, (72h), Algae, 1000 mg/L		
LL50, (96h), fish, >1000mg/L		
Bis(nonylphenyl)amine, CAS: 36878-20-3		
EC50, (48h), Invertebrates, 100 mg/L		
EL50, (72h), Algae, 100 mg/L		
NOELR, (33d), fish, 10 mg/L		
NOELR, (21d), Invertebrates, 4.45 mg/L		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
EL50, (48h), Invertebrates, 10 g/L		
NOELR, (14d), fish, 1 mg/L		
LL50, (96h), Invertebrates, 10 g/L		
LL50, (96h), fish, 100 mg/L		
Benzenepropanoic acid, 3,5-bis(1,1-dimethyl-ethyl)-4-hydroy-, C7-C9-branched alkyl ester, CAS: 125643-61-0		
LC50, (14d), fish, 100 mg/L		
EC50, (48h), Invertebrates, 8.2 - 1000000 µg		
EC50, (72h), Algae, 180 - 3000000 ng/L		
EC50, (3h), Water microorganisms, 100 - 1000 mg/L		
NOEC, (21d), Invertebrates, 10 μg/L		
NOEC, (33d), fish, 360 μg/L		

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

Biological degradability

The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 11 / 14

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the authorities if necessary.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

In according to RoHS!

Waste no. (recommended) 130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Page 12 / 14 Version 2.0. Supersedes version: 1.0

14.3 Transport hazard class(es)

Transport by land according to ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID

nο

Inland navigation (ADN)

no

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable



Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 13 / 14

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707

- Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

- Annex I (REACH) The product is not subject to Annex I restrictions.

- Annex XIV (REACH) According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain

any substances ≥ 0.1% that are subject to authorisation.

- Annex XVII (REACH) According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains ≥ 0.1%

of substances with the following restrictions. 75

According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to

any restrictions.

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

NATIONAL REGULATIONS (UK): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) not relevant

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H317 May cause an allergic skin reaction.

H413 May cause long lasting harmful effects to aquatic life.

H304 May be fatal if swallowed and enters airways.

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 24.04.2024, Revision 24.04.2024

Version 2.0. Supersedes version: 1.0

Page 14 / 14

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average

TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position none