

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

hydraulic fluid
Article number: 24704
UFI: 6YD6-S22Y-A00N-7YXN

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Hydraulics oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Irrit. 2: H315 Causes skin irritation.
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms



Signal word

WARNING

Hazard statements

H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves / protective clothing.
P332+P313 If skin irritation occurs: Get medical advice / attention.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Special labelling

Contains: reaction products of P-/N-/S-containing compounds with propionic acid, 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid. EUH208 May produce an allergic reaction.

2.3 Other hazards

Environmental hazards

Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - <60	Distillates (petroleum), hydrotreated light naphthenic CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2 GHS/CLP: Asp. Tox. 1: H304
15 - <30	Distillates (petroleum), hydrotreated middle CAS: 64742-46-7, EINECS/ELINCS: 265-148-2, EU-INDEX: 649-221-00-X GHS/CLP: Acute Tox. 4: H332 - Asp. Tox. 1: H304 - Skin Irrit. 2: H315 - Aquatic Chronic 2: H411
15 - <30	Distillates (petroleum), hydrotreated light paraffinic CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - <10	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX GHS/CLP: Asp. Tox. 1: H304
5 - <10	2-Propenoic acid,2-methyl-, dodecyl ester,polymer with eicosyl2-methyl-2-propenoate, hexadecyl2-methyl-2-propenoate, methyl2-methyl-2-propenoate, octadecyl2-methyl-2-propenoate, pentadecyl2-methyl-2-propenoate, tetradecyl and tridecyl2-methyl-2-propenoate GHS/CLP: Eye Irrit. 2: H319
2,5 - <5	Base oil CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, Reg-No.: 01-2119474878-16-XXXX GHS/CLP: Asp. Tox. 1: H304
<0.5	2,6-di-tert-butylphenol CAS: 128-39-2, EINECS/ELINCS: 204-884-0, Reg-No.: 01-2119490822-33-XXXX GHS/CLP: Skin Irrit. 2: H315 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400, M-Factor (acute): 1, M-Factor (chronic): 1
0,1 - <0,3	Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9–C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione EINECS/ELINCS: 947-263-6, Reg-No.: 01-2120761103-66-XXXX GHS/CLP: Repr. 2: H361 - Skin Irrit. 2: H315 - Aquatic Chronic 4: H413
<0.25	reaction products of P-/N-/S-containing compounds with propionic acid EINECS/ELINCS: 939-700-4, Reg-No.: 01-2119982395-25 GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1B: H317 - Aquatic Acute 1: H400 - Aquatic Chronic 2: H411
<0.25	3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid CAS: 268567-32-4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31 GHS/CLP: Eye Dam. 1: H318 - Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
If swallowed or in the event of vomiting, risk of product entering the lungs.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Fire extinguishing method of surrounding areas must be considered. Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Fire class (DIN EN 2): B

Do not smoke.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Distillates (petroleum), hydrotreated light paraffinic
CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
Long-term exposure: 5 mg/m ³ , ACGIH TLV (OIL MIST)

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
Industrial, inhalative, Long-term - systemic effects, 70,61 mg/m ³
Industrial, dermal, Long-term - systemic effects, 11,25 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 20,9 mg/m ³
general population, oral, Long-term - systemic effects, 6,75 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 6,75 mg/kg bw/day
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
Industrial, inhalative, Long-term - systemic effects, 4,4 mg/m ³ (AF=25)
Industrial, dermal, Long-term - systemic effects, 1,25 mg/kg bw/d (AF=100)
general population, inhalative, Long-term - systemic effects, 1,1 mg/m ³ (AF=50)
general population, dermal, Long-term - systemic effects, 0,6 mg/kg bw/d (AF=200)
general population, oral, Long-term - systemic effects, 0,6 mg/kg bw/d (AF=200)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1,19 mg/m ³
general population, inhalative, Long-term - systemic effects, 740 µg/kg bw/day
reaction products of P-/N-/S-containing compounds with propionic acid
Industrial, inhalative, Long-term - systemic effects, 1,3 mg/m ³ (AF=30)
Industrial, dermal, Long-term - systemic effects, 0,4 mg/kg bw/d (AF=120)
general population, dermal, Long-term - systemic effects, 0,2 mg/kg bw/d (AF=240)
general population, inhalative, Long-term - systemic effects, 0,3 mg/m ³ (AF=60)
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
Industrial, inhalative, Long-term - systemic effects, 3,72 mg/m ³ (AF= 18)
Industrial, dermal, Long-term - systemic effects, 1,04 mg/kg bw/d (AF= 72)
general population, dermal, Long-term - systemic effects, 0,625 mg/kg bw/d (AF= 120)
general population, inhalative, Long-term - systemic effects, 1,1 mg/m ³ (AF= 30)

PNEC

general population, oral, Long-term - systemic effects, 0.625 mg/kg bw/d (AF= 120)
Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
freshwater, 700 ng/L
seawater, 70 ng/L
sewage treatment plants (STP), 10 mg/L
sediment (freshwater), 317 µg/kg sediment dw
sediment (seawater), 31.7 µg/kg sediment dw
soil, 697 µg/kg soil dw
oral (food), 60 mg/kg food
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
freshwater, 0.072 mg/L (AF=50)
seawater, 0.007 mg/L (AF=500)
sewage treatment plants (STP), 10 mg/l (AF=10)
sediment (freshwater), 23 mg/kg dw
sediment (seawater), 2.3 mg/kg dw
soil, 4.54 mg/kg dw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
oral (food), 9,33 mg/kg food
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9.33 mg/kg food
reaction products of P-/N-/S-containing compounds with propionic acid
freshwater, 0,001 mg/l (AF=1000)
seawater, 0 mg/l (AF=10.000)
sewage treatment plants (STP), 0,69 mg/l (AF=100)
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9–C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
freshwater, 0.496 mg/L (AF= 1000)
seawater, 0.05 mg/L (AF= 10 000)
sewage treatment plants (STP), 100 mg/L (AF= 10)
sediment (freshwater), 3 772.830 g/kg dw
sediment (seawater), 377.28 g/kg dw
soil, 3 935.35 g/kg dw

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. >0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	See SECTION 6+7.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	green
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	126 (ISO 2592)
Flammability	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/cm ³]	ca. 0,867 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	not determined
Kinematic viscosity	ca. 21 mm ² /s (40°C) (DIN 51562/T1) 6,3 mm ² /s (100°C)
Relative vapour density	not determined
Melting point [°C]	not determined
Auto-ignition temperature [°C]	not determined
Decomposition temperature [°C]	> 300
Particle characteristics	No information available.

9.2 Other information

Pour point: ca. -51 (ISO 3016)

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 300°C.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, oral, Rat, > 5000 mg/kg
2,6-di-tert-butylphenol, CAS: 128-39-2
LD50, oral, Rat, 5000 mg/kg bw
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, oral, Rat, > 2000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, oral, Rat, 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, oral, Rat, 5000 mg/kg bw
Base oil, CAS: 72623-86-0
LD50, oral, Rat, > 2001 mg/kg
reaction products of P-/N-/S-containing compounds with propionic acid
LD50, oral, Rat, 3313 mg/kg bw
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
LD50, oral, Rat (female), > 2000 mg/kg bw, OECD 423
NOAEL, oral, Rat, 75 mg/kg bw/day

Acute dermal toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, dermal, Rabbit, > 2000 mg/kg
2,6-di-tert-butylphenol, CAS: 128-39-2
LD0, dermal, Rat, 1000 - 33000 mg/kg bw
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, dermal, Rat, > 2000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw
Base oil, CAS: 72623-86-0
LD50, dermal, Rabbit, > 2001 mg/kg
reaction products of P-/N-/S-containing compounds with propionic acid
LD50, dermal, > 2000 mg/kg bw

Acute inhalational toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalation (vapour), >20 mg/L
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LC50, inhalative, Rat, 5000 mg/m ³ /4h
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air, 4h
Base oil, CAS: 72623-86-0
LC50, inhalative, Rat, > 5,53 mg/l/4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Eye, non-irritating

Skin corrosion/irritation Irritant

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
dermal, non-irritating

Respiratory or skin sensitisation May produce an allergic reaction.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
inhalative, no adverse effect observed

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
NOAEL, oral, Rat, 100 mg/kg bw/day, OECD 407, negativ
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOAEC, inhalative, Rat, 980 mg/m ³ (subacute), no adverse effect observed
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, dermal, mouse, 100 mg/kg bw/day (chronic), The effects observed are not sufficient for classification.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
2,6-di-tert-butylphenol, CAS: 128-39-2
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 421, negativ, Effect on fertility,
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 414, negativ, Effect on developmental toxicity,
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- Development

Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
2,6-di-tert-butylphenol, CAS: 128-39-2
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 421, negativ, Effect on fertility,
NOAEL, oral, Rat, 150 mg/kg bw/day, OECD 414, negativ, Effect on developmental toxicity,

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information none

SECTION 12: Ecological information

12.1 Toxicity

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
LC50, (21d), Invertebrates, 230 µg/L
LC50, (14d), fish, 1 mg/L
LC50, (4d), fish, 1.4 mg/L
EC50, (4d), Algae, 1.2 - 3.9 mg/L
EC50, (72h), Algae, 1.4 - 3.6 mg/L
EC50, (48h), Algae, 1.7 - 3.5 mg/L
EC50, (24h), Algae, 1.7 - 2.3 mg/L
EC50, (48h), Invertebrates, 450 µg/L
EC50, (24h), Invertebrates, 590 µg/L
EC50, (21d), Invertebrates, 140 µg/L
LC0, (48h), Invertebrates, 76 µg/L
NOEC, (21d), Invertebrates, 35 µg/L
NOEC, (96h), Algae, 640 - 2100 µg/L
NOEC, (14d), fish, 300 µg/L
LOEC, (21d), Invertebrates, 86 µg/L
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LC50, (96h), fish, 54 mg/l
EC50, (48h), Daphnia magna, 53 mg/l
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOELR, (14d), fish, 1 g/L
LL50, (4d), Invertebrates, 10 g/L
LL50, (4d), fish, 100 mg/L
reaction products of P-/N-/S-containing compounds with propionic acid
LC50, (96h), 1 - 10 mg/l
EC50, (48h), Daphnia magna, 1 - 10 mg/l
Reaction products of fatty acids, C16-18, C18 unsatd. with Amines, polyethylenepoly-, triethylenetetramine fraction and 3-(C9-C15, C12 rich, alk-1-enyl)dihydro-2,5-furandione
LC50, (96h), fish, 1000 mg/L
EC50, (48h), Invertebrates, 1000 mg/L
EC50, (72h), Algae, 370 - 496 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant not determined

Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.
Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS
Inland navigation (ADN)	NO DANGEROUS GOODS
Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EG); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EG) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EG) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex I (REACH)	The product is not subject to Annex I restrictions.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances \geq 0.1% that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains \geq 0.1% of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is subject to the following restrictions. 3
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for young people.
- VOC (2010/75/CE)	0%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H412 Harmful to aquatic life with long lasting effects.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.
H413 May cause long lasting harmful effects to aquatic life.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Irrit. 2: H315 Causes skin irritation. (Calculation method)
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

1.3, 3.2, 4.2, 8.1, 8.2, 9.1, 9.2, 11.1, 11.2, 12.1, 12.6, 12.7, 15.1, 16.2, 16.3