

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 1 / 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

automatic transmission fluid (ATF)

Article number: 10 92 2806, 10 98 0018, 10 92 6680, 10 92 6681, 33 11 1641

UFI: 4051-421H-000D-R1X6

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information

info@swag.de

Safety Data Sheet

info@swag.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.

2.2 Label elements

Hazard pictograms

The product is required to be labelled in accordance with regulation CLP.



Signal word

WARNING

Contains:

reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

1,1'-[iminobis(ethyleneiminoethylene)]bis[3-(octadecenyl)pyrrolidine-2,5-dione]

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves.

P332+P313 If skin irritation occurs: Get medical advice / attention.

P501 Dispose of contents/container to approved disposal company or municipal collection point.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 2 / 16

2.3 Other hazards

Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances. Contains no ingredients with endocrine-disrupting properties.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
15 - <30	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX GHS/CLP: Asp. Tox. 1: H304
5 - < 15	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract) CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, EU-INDEX: 649-221-00-X GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), hydrotreated light paraffinic CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), hydrotreated light naphthenic CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2, Reg-No.: 01-2119480375-34-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates EINECS/ELINCS: 417-450-2, EU-INDEX: 650-042-00-4, Reg-No.: 01-0000016426-70-XXXX GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 3: H412 - Eye Irrit. 2: H319 - Skin Irrit. 2: H315
1 - < 2,5	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract) CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt) CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX GHS/CLP: Asp. Tox. 1: H304
0,1 - < 1	1,1'-[iminobis(ethyleneiminoethylene)]bis[3-(octadecenyl)pyrrolidine-2,5-dione] CAS: 64051-50-9, EINECS/ELINCS: 264-637-8 GHS/CLP: Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 3 / 16

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Fire extinguishing method of surrounding areas must be considered.
Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used Full water jet.

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).
Nitrogen oxides (NO_x).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 4 / 16

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

The product is combustible.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Do not store together with oxidizing agents.

Keep container tightly closed.

Keep container in a well-ventilated place.

Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 5 / 16

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Distillates (petroleum), hydrotreated light naphthenic
CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2, Reg-No.: 01-2119480375-34-XXXX
Long-term exposure: 1200 mg/m ³
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX
Long-term exposure: 1200 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic
CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
Long-term exposure: 5 mg/m ³ , ACGIH TLV (OIL MIST)

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Industrial, inhalative, Long-term - local effects, 5,4 mg/m ³ /8h (Aerosol)
general population, inhalative, Long-term - local effects, 1,2 mg/m ³ /24h (Aerosol)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1,19 mg/m ³
general population, inhalative, Long-term - systemic effects, 740 µg/kg bw/day
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day
2,7 mg/m ³
general population, inhalative, Long-term - systemic effects, 1,19 mg/m ³

PNEC

Substance

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
oral (food), 9,33 mg/kg food
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9,33 mg/kg food
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
oral (food), 9,33 mg/kg food

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3). > 0,4 mm: Neoprene, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	red
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	>170 (DIN ISO 2592)
Flammability	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/cm ³]	ca. 0,849 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	ca. 33 mm ² /s (40°C) (DIN 51562/T1) ca. 7,4 mm ² /s (100°C) (DIN 51562/T1)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

Pour point: ca. -42 (DIN ISO 3016)

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong acids.
Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 100°C.



**SWAG Autoteile GmbH
42117 Wuppertal**

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 8 / 16

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 9 / 16

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LD50, oral, Rat, > 5000 mg/kg
reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates
LD50, oral, Rat, > 2000 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)
NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, oral, Rat, > 5000 mg/kg (OECD 420)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, oral, Rat, 5000 mg/kg bw
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, oral, Rat, > 5000 mg/kg

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LD50, dermal, Rabbit, > 5000 mg/kg
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 403)
NOAEL, dermal, Rat, >2000 mg/kg bw (OECD 414)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, dermal, Rabbit, > 5000 mg/kg (OECD 402)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, dermal, Rabbit, > 2000 mg/kg

Acute inhalational toxicity

Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalation (vapour), >20 mg/L

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0 Page 10 / 16

Substance
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LC50, inhalative, Rat, > 5000 mg/m ³ (4h)
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LC50, inhalative, Rat, >5,53 mg/l air (OECD 403)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LC50, inhalative, Rat, > 5 mg/l /4h(Aerosol) (OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LC50, inhalative, Rat, > 5 mg/l/4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Eye, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating

Respiratory or skin sensitisation May cause an allergic skin reaction.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-sensitizing
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEC, inhalative, Rat, 980 mg/m ³ , no adverse effect observed
LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m ³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0

Page 11 / 16

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
in vitro, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard

Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information

none

SECTION 12: Ecological information

12.1 Toxicity

Substance
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >= 100 mg/l (OECD 201)
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
EL50, (72h), Pseudokirchneriella subcapitata, > 100 mg/l (OECD 201)
EL50, (48h), Daphnia magna, > 10000 mg/l (OECD 202)
LL50, (96h), Oncorhynchus mykiss, > 100 mg/l (OECD 203)
NOAEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOAEL, Oncorhynchus mykiss, > 1000 mg/l (14/28d)(QSAR Petrotox))
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOELR, (14d), fish, 1 g/L
LL50, (4d), Invertebrates, 10 g/L
LL50, (4d), fish, 100 mg/L
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
EL50, (48h), Daphnia magna, > 1000 mg/l
LL50, (96h), Pimephales promelas, > 100 mg/l
NOEL, (72h), Pseudokirchneriella subcapitata, 100 mg/L (OECD 201, KS=2)

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

Biological degradability

The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0 Page 13 / 16

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102
150104
150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0 Page 14 / 16

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0 Page 15 / 16

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex I (REACH)	The product is not subject to Annex I restrictions.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances \geq 0.1% that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains \geq 0.1% of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is subject to the following restrictions. 3
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for young people.
- VOC (2010/75/CE)	<2 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 17.04.2024, Revision 28.02.2024

Version 14.1. Supersedes version: 14.0 Page 16 / 16

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Modified position

none