

# OEM SPECIFIC

## 75W80

*This is an extreme-pressure lubricant for gear boxes, specially formulated, made of specially selected, high-quality base oils and a customized additive package, to satisfy the highest service conditions: high speed, shockloads, high torque at low speeds and multiple synchromesh compatibility.*

### APPLICATIONS

*It is recommended for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.*

### FEATURES

*Frictional properties : smooth shift performance.*

*Anti-wear protection : long transmission life.*

*Extended oil life : proven resistance to oil degradation.*

### SPECIFICATION LEVEL

<b>API</b>	GL-5	<b>OPEL</b>	GM 1940776
<b>BMW</b>	23007533513/818	<b>OPEL</b>	GM 1940182
<b>BMW</b>	23001434404	<b>OPEL</b>	GM 1940757
<b>BMW</b>	83220309031	<b>OPEL</b>	GM 1940768
<b>BMW</b>	83220403247	<b>VOLVO</b>	97308
<b>BMW</b>	83227533818	<b>VW</b>	501 50
<b>FORD</b>	WSD-M2C200-C/C2/C3	<b>VW</b>	G 005 000
<b>MIL</b>	MIL-L-2105 D	<b>VW</b>	G 052 911

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	54,5
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10,5
Viscosity index	ASTM D2270		186
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**