



Genuine Quality.
Durable Trust.



Hydraulic oil HLP 46/

ISO 11158

9.58090

DT Spare Parts Hydraulic Oil 9.58090 is a high-quality hydraulic oil that fulfils all requirements pursuant to DIN 51524-2 and ISO 11158. It provides very good protection against wear and corrosion, and a good compatibility with material coatings and sealing materials. It is used in mobile and stationary hydraulic systems, such as construction machinery and vehicles, machine tools, and compactors. Nevertheless, it can also be used to lubricate low-stress roller bearings and slide bearings, and gearboxes if the manufacturer permits these units.

Specifications:

- DIN 51 524-2 (HM)
- GM LS-2
- AIST 126
- ISO 11158 (HM)
- ASTM D 6158 (HM)
- JCMAS P041 HK Hydraulic specification
- Bosch Rexroth RDE 90235
- Parker (Denison) HF-0, HF-1, HF-2 (HM)
- Eaton E-FDGN-TBoo2-E
- SAE MS 1004 (HM)
- Fives P68, P69, P70 (HM)
- SEB 181222
- GB 111158.1-2011 (L-HL, L.HM)

Information is subject to change without notice. The vehicle manufacturer's specifications apply respectively. More information can be found on the safety data sheet.

Shop 24/7 here:
partnerportal.dieseltechnic.com

