



THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval


of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0034*01

Reason for extension: Fits also VW LT 1996

SECTION I

0.1	Make (trade name of manufacturer)	: Bosal
0.2.	Type and general commercial description(s)	: 901 2095
0.3.	Means of identification of type if marked on the component	: Approval number
0.3.1.	Location of the marking	: on type plate
0.5.	Name and address of manufacturer	: Bosal Postbus 168 4920 AD MADE
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC approval mark	: on type plate
0.8.	Name(s) and address(es) of assembly plants	: see information document (Annex III), item 0.8



SECTION II

1. Additional information (where applicable)

- : see Appendix I
- 2. Technical sevice responsible for carrying out the tests

: RDW Testbaan|Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report

: 01-03-1995

4. Number of test report

: TC-68-94/20-029/95

5. Remarks (if any)

: see Appendix I


6. Place

: Zoetermeer

7. Date

0 6. DEC 1996

8. Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4.

651-8902

Appendix I

to EEC type-approval certificate No: e4*94/20*0034*01 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

: see fitting instructions

1.3. Maximum D-value : 12.49 kN

1.4. Maximum vertical load S at the coupling point : 100 kg

1.5. Maximum load U at the fifth wheel coupling point : -- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

pecial types of vehicles : see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

see fitting instructions

5. Remarks : The fitting of the towbar on the vehicle must be checked according

annexI nr.5.10,according the presciptions mentionend in annex

VII

