



THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0936*00

Reason for extension:

SECTION I

0.1	Make (trade name of manufacturer)	: Le Rapide
0.2.	Type and general commercial description(s)	: 017940
0.3.	Means of identification of type if marked on the component	: Approval number
0.3.1.	Location of the marking	: on type plate RDW
0.5.	Name and address of manufacturer	: Bosal le Rapide Avenue des Monts de Champagne 51490 BEINE NAUROY / FRANCE

- 0.7. In the case of components and separate technical units, location and method of affixing of the EEC approval mark
- 0.8. Name(s) and address(es) of assembly plants

: on type plate

: see information document

(Annex III), item 0.8

ype-approval number : e4*94/20*0936*00

SECTION II

1. Additional information (where applicable)

: see Appendix I

2. Technical service responsible for carrying out the tests

: RDW Testbaan|Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report

: 04-11-1997

4. Number of test report

: TCL-94/20-357/97

5. Remarks (if any)

: see Appendix I

6. Place

: Zoetermeer

7. Date

D 8 DEC 799

8. Signature

9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:

- Application form relating to Annex III and annexed drawings
- Drawings and instructions for attachment
- Fitting instructions
- Testreport, as mentioned in item 4.

É. Plancius

Appendix I to EEC type-approval certificate No: e4*94/20*0936*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

see fitting instructions

1.3. Maximum D-value : 6,39 kN

1.4. Maximum vertical load S at the coupling point : 50 kg

1.5. Maximum load U at the fifth wheel coupling point : -- ton

()1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to

special types of vehicles : see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

see fitting instructions

TE MAINTISTISTA AL
RDW

5. Remarks :

The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I

par.5.10.