

RDW

NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval

ge^{tre to}

- extension of type-approval

- refusal of type-approval

- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*2426*00

Reason for extension:

SECTION I

0.1.	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	033211
0.3.	Means of identification of type marked on the component	:	Type approval number
0.3.1.	Location of that marking	:	On type plate
0.5.	Name and address of manufacturer	•	Bosal Tweede industrieweg 6 4921 XH Made, the Netherlands
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC type approval mark	:	On type plate
0.8.	Address(es) of assembly plant(s)	:	See information document (annex III, item 0.8)



5 C 1301a

Phone +31 79 3458143 Fax +31 79 3458043

wp5163c.r00/1:3/e

Type-approval number: e4*94/20*2426*00

Here and

SECTION II

1.	Additional information (where applicable)	:	See Appendix I
2.	Technical service responsible for carrying out the tests	:	RDW Testbaan Centrum Talingweg 76 8218 NX Lelystad
3.	Date of test report	:	07-01-2004
4.	Number of test report	:	RDW-94/20-3517
5.	Remarks (if any)	:	See Appendix I
6.	Place	:	Zoetermeer
7.	Date	:	07-01-2004
8.	Signature	:	RDW J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No : e4*94/20*2426*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information				
1.1.	Class of the type of coupling	:	A50-X		
1.2.	Categories or types of vehicles for which the device is designed or restricted	3	See fitting instructions		
1.3.	Maximum D-value	:	9.90	kN	
1.4.	Maximum vertical load S at the coupling point		75	kg	
1.5	Maximum load U at the fifth wheel coupling point	:		ton	
1.6.	Maximum V-value	:	an an ar ar ar ar	kN	
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	:	See fitting instructions		
1.8	Information on the fitting of special towing	:	See fitting inst	ructions	

- brackets or mounting plates
- Remarks: The installation of the coupling device to the vehicle must be checked according to 5. requirements of Annex VII, see Annex I, par.5.10.



general

Phone +31 79 3458143 Fax +31 79 3458043